

Enterprise HD IP Phone

—Wi-Fi/Bluetooth IP Phone UC926E

UC926E is an innovative Gigabit Color IP Phone. It supports up to 5-way conference. UC926E is optimized for executive use for major decision makers, administrative assistants and those working with bandwidth-intensive application on collocated PCs. Programmable keys could be configured as IP PBX features like BLF, SCA, Intercom, Call Park and many other features. The high-resolution TFT-LCD and HD Voice bring you the lifelike visual and audio experience.



Key Features and Benefits

1. HD Audio

UC926E not only upgrades its hardware such as handset, hands-free components and headset, but also supports Opus and other sound codecs, creating a clearer voice, and achieving HD sound quality under different network bandwidths, making remote communication close at hand and helping your team to more smoothly.

2. Industry-leading Connectivity

UC926E has a built-in Bluetooth 4.0 module and supports Bluetooth headsets, free from limits of wires. At the same time, it has built-in 2.4GHz Wi-Fi, needs no network cables and realizes swift deployment.

3. Powerful Expansibility

UC926E supports Gigabit Ethernet port and PoE, which makes network connection more flexible and convenient; supports EHS30 adapter, which is convenient and fast to use together; it also can connect up to 6 color-screen expansion modules UC46 which can be programmed with up to 240 paperless DSS keys, supports wall hanging to meet user needs in different scenarios.

4. Efficient Installation and Provisioning

You can use Htek RPS to achieve fast and efficient deployment. Users do not need to manually configure and upgrade the phone; instead, just power on and connect to the Internet, and the phone can be automatically deployed, saving a lot of time and cost, and realizing "Zero Touch Provisioning" in the true sense. In addition, it supports advanced tools such as Htek Device Management System (HDMS), so firmware update and device management can also be completed through remote operation, making the phone easy to use, easy to deploy, and easy to manage.

- 4.3" 480x272-pixel color display with backlight
- 16 SIP accounts, 8 feature keys, 10 line keys
- Support up to 36 paperless DSS keys
- Local phonebook up to 1000 entries
- HD Voice: HD Codec, HD Speaker, HD Handset
- Dual-port Gigabit Ethernet
- Dual firmware images
- PoE support
- Built-in 2.4GHz Wi-Fi
- Built-in Bluetooth 4.0
- Stand with 2 adjustable angles
- Wall mountable
- Support HDMS

Phone Features

- 16 SIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Redial, call return, auto answer, direct IP call
- 5-way conferencing
- Group listening, SMS, emergency call
- Ring tone selection/provisioning
- Set date time automatically or manually
- Dial plan for each account
- RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
- Action URL/URI
- USB port (2.0 compliant) for:
 - USB call recording through USB flash drive
 - USB storage(screen saver, wallpaper)
 - USB headset

Audio Features

- HD Voice: HD Speaker, HD Handset, HD codec
- Codecs: iLBC, G.722, G.711(A/μ), Opus, G.723.1, G.729AB, G.726-32, G.722.1
- DTMF: In-band, RFC 2833, SIP INFO
- Full-duplex hands-free speakerphone with AEC
- AEC, VAD, AGC, CNG, PLC, AJB

Directory

- Local phonebook up to 10000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Black list

IP-PBX Features

- Busy Lamp Field (BLF)
- Bridged Line Appearance (BLA)
- Anonymous call, anonymous call rejection
- Message Waiting Indicator (MWI), voice mail
- Intercom, paging
- Call park, call pickup
- Music on hold
- Hot-desking

Display and Indicator

- 4.3" 480x272-pixel color display with backlight
- 24 bit depth color
- LED for call and message waiting indication
- Dual-color(red or green) illuminated
- LEDs for line status information
- Wallpaper, national language selection
- Intuitive user interface with icons and soft keys
- Caller ID with name, number and photo
- Wi-Fi/Bluetooth supported

Feature keys

- 10 line keys with LED
- 10 line keys can be programmed up to 36 Paperless DSS keys (4-page view)
- 8 feature keys: voice mail, headset, mute, speaker, conference, hold, transfer, redial
- 4 context-sensitive soft keys
- 6 Navigation keys(include cancel key) and volume control keys

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 3
- IEEE 802.3az Green Energy Efficient Ethernet
- 1xRJ9 (4P4C) handset port
- 1xRJ9 (4P4C) headset port
- 1 x RJ12 (6P6C) EXT port
- Support EHS
- Support up to 6 Expansion Modules

Physical Features

- Stand with 2 adjustable angles
- Wall mountable
- External universal AC adapter : AC 100~240V input and DC 5V/1.2A output
- Power consumption (PSU): 2.0~4.6W
- Power consumption (PoE): 2.5~5.5W
- Operating humidity: 10~95%
- Operating temperature: -10~50°C

Management

- Configuration: browser/LCD-Menu/auto-provision
- Auto provision via HTTP/HTTPS/FTP/TFTP
- Auto-provision with PnP
- Reset to factory, reboot
- Local tracing log export, system log
- Phone lock for personal privacy protection

Wi-Fi/Bluetooth

- Wi-Fi:
 - Network Standard: IEEE802.11b/g/n
 - Transmission Rate: 150Mbps
 - Frequency Range: 2.4GHz
- Bluetooth:
 - Bluetooth specification:V4.0+HSsystem
 - Enhanced Data Rate (EDR) compliant for both 2Mbps and3Mbps supported
 - Bluetooth frequency range: 2.402GHz-2.480GHz
 - Compatible with Bluetooth specification V4.2,
 - Backward compatible with Bluetooth1.1 1.2 2.0 and 3.0 for wide-ranging use


Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server/proxy redundancy
- NAT Traversal: STUN mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- DNS-NAPTR/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS DSCP
- Transport Layer Security(TLS1.2), SRTP, ZRTP
- HTTPS certificate manager
- AES encryption for configuration file
- Digest authentication using MD5/MD5-sess
- IEEE802.1X/OpenVPN
- IPv4/IPv6, LLDP/CDP/DHCP VLAN

Package Features

- Package content:
 - Phone Device*1pcs
 - Footstand*1pcs
 - Handset*1pcs
 - Handset Cord*1pcs
 - Ethernet Cable*1pcs
 - Quick Reference Manual
 - Power Adapter (Optional)
- Qty/CTN: 10 pcs
- N.W/CTN: 13.92 kg
- G.W/CTN: 15.17 kg
- Phonebox Size: 245mm(L)*225mm(W)*100mm(H)
- Carton Meas:525mm(L)*510mm(W)*245mm(H)

Compliance



Learn More

To find out how Htek solutions can help your organization, visit us at www.htek.com or mail to sales@htek.com.



About Htek

Htek is a world-class designer and manufacturer of enterprise IP phones and gateways. Since 2005, Htek (aka Hanlong Technology) has provided customers in over 90 countries worldwide with high-quality VoIP products. Htek's UC900U series IP phones continue the tradition by focusing on cutting-edge features, broad SIP compatibility, great value, and an industry-leading warranty. Htek distributes its products via channel partners, and custom designs and rebrands products for large partners such as ITSPs. Nanjing Hanlong Technology Co., Ltd. is a private company headquartered in Nanjing, China, with offices in LATAM, North America and Europe.

Copyright © 2022 NANJING HANLONG TECHNOLOGY CO., LTD.

Copyright © 2022 Nanjing Hanlong Technology Co., Ltd. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Nanjing Hanlong Technology Co., Ltd.

Technical Support

Visit Htek official website (<http://www.htek.com/>) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Htek support system (<http://support.htek.com/>) to submit all your technical issues.



NANJING HANLONG TECHNOLOGY CO., LTD.

Tel: 0086-25-84658050 | Fax: 0086-25-84658319 | Mail: support@htek.com | Web: www.htek.com

Add: 5th Floor, Building No.1, Huashen TechPark, No.10 Huashenmiao, Yuhuatai District, Nanjing, 210012, China

Copyright: ©2022 Nanjing Hanlong Technology Co., Ltd. All rights reserved.